


Linear Patterns - Single Grid

MEME Micro-Measurements

VISHAY
PRECISION GROUP


Transducer-Class® Strain Gages

GAGE PATTERN	Actual size shown. Enlarged when necessary for definition	GAGE DESIGNATION See Note 1	RES. IN OHMS	STANDARD CREEP CODE	ENCAPSU- LATION OPTION AVAILABLE
DIMENSIONS	inch millimeter				




Miniature high-resistance pattern.

GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH				
0.031	0.08	0.062	0.062				
0.78	2.0	1.57	1.57				
MATRIX SIZE				N2K-XX-S118M-10C/DP	$1000 \pm 0.2\%$	M	E2
				TK-XX-S118M-10C/DP	$1000 \pm 0.2\%$	M	E2



Miniature high-resistance pattern.

GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH				
0.060	0.13	0.050	0.050				
1.52	3.3	1.27	1.27				
MATRIX SIZE				N2K-XX-S065R-10C/DP	$1000 \pm 0.15\%$	R	E2
				TK-XX-S065R-10C/DP	$1000 \pm 0.15\%$	R	E2
				SK-XX-S065R-10C	$1000 \pm 0.3\%$	R	



General-purpose miniature patterns.

NOTE: Matrix and overall length of J2A and J5K patterns will be slightly longer than dimensions shown.

GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH				
0.062	0.12	0.062	0.062				
1.57	3.1	1.57	1.57				
MATRIX SIZE				N2A-XX-S071P-350	$350 \pm 0.1\%$	P	E2
				J2A-XX-S183P-350	$350 \pm 0.3\%$	P	
				N2K-XX-S075P-350/DP	$350 \pm 0.15\%$	P	
				TK-XX-S075P-350/DP	$350 \pm 0.15\%$	P	
				J5K-XX-S104P-350/DP	$350 \pm 0.3\%$	P	
				SK-XX-S075P-350	$350 \pm 0.3\%$	P	


Note 1: Products shown in bold are not RoHS compliant.

Transducer-Class® Strain Gages

GAGE PATTERN	Actual size shown. Enlarged when necessary for definition	GAGE DESIGNATION See Note 1	RES. IN OHMS	STANDARD CREEP CODE	ENCAPSULATION OPTION AVAILABLE
DIMENSIONS	inch millimeter				

				The most popular small gage pattern.			
				N2A-XX-S148P-120 N2A-XX-S106N-175 N2A-XX-T001N-350 N2A-XX-T010P-10C J2A-XX-S148P-120 J2A-XX-S106N-175 J2A-XX-S047K-350 J2A-XX-S110K-10C N2K-XX-S123R-175/DP N2K-XX-T009N-350/DP N2K-XX-S072R-10C/DP TK-XX-S123R-175/DP TK-XX-T009Q-350/DP TK-XX-S072R-10C/DP J5K-XX-S103Q-350/DP SK-XX-S074R-350 SK-XX-S072R-10C	P N P P N K K R N R R Q R Q R R		
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH	120 ± 0.15% 175 ± 0.15% 350 ± 0.15% 1000 ± 0.15% 120 ± 0.3% 175 ± 0.3% 350 ± 0.3% 1000 ± 0.3% 175 ± 0.15% 350 ± 0.15% 1000 ± 0.15% 175 ± 0.15% 350 ± 0.15% 1000 ± 0.15% 350 ± 0.3% 350 ± 0.3% 1000 ± 0.3%	E2 E2 E2 E2 E2 E2 E2 E2 E2 E2 E2 E2 E2 E2 E2 E2 E2		
0.060	0.15	0.100	0.100				
1.52	3.8	2.54	2.54				
MATRIX SIZE	0.22 L x 0.16 W	5.6 L x 4.1 W					

				Higher-power-dissipation versions of the T001/T009 patterns.			
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH	N2A-XX-T002Q-350 N2K-XX-T003Q-350/DP TK-XX-T003Q-350/DP	350 ± 0.15% 350 ± 0.15% 350 ± 0.15%	Q Q Q	E2 E2 E2
0.060	0.17	0.180	0.180				
1.52	4.3	4.57	4.57				
MATRIX SIZE	0.24 L x 0.24 W	6.1 L x 6.1 W					

				One of the most popular gage sizes.			
				†Overall length on S078/S080 is 0.25 in (6.4mm). Matrix length will also increase slightly.			
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH	N2A-XX-S107N-120 N2A-XX-T004R-350 N2A-XX-T096R-500 N2A-XX-S108N-10C J2A-XX-S108N-10C N2K-XX-T005R-350/DP N2K-XX-S163R-500/DP N2K-XX-S078W-10C/DP TK-XX-T005R-350/DP TK-XX-S078W-10C/DP SK-XX-S080W-350 SK-XX-S078W-10C	120 ± 0.15% 350 ± 0.15% 500 ± 0.15% 1000 ± 0.15% 1000 ± 0.3% 350 ± 0.15% 500 ± 0.15% 1000 ± 0.15% 350 ± 0.15% 1000 ± 0.15% 350 ± 0.3% 1000 ± 0.3%	N R R N N R R W R W W	E2 E2 E2 E2 E2 E2 E2 E2 E2 E2 E2 E2
0.125	0.23†	0.125	0.125				
3.18	5.8†	3.18	3.18				
MATRIX SIZE	0.29 L x 0.19 W	7.4 L x 4.8 W					

Note 1: Products shown in bold are not RoHS compliant.


Linear Patterns - Single Grid

MEME Micro-Measurements


VISHAY
PRECISION GROUP

Transducer-Class® Strain Gages


GAGE PATTERN	Actual size shown. Enlarged when necessary for definition	GAGE DESIGNATION	RES. IN OHMS	STANDARD CREEP CODE	ENCAPSULATION OPTION AVAILABLE
DIMENSIONS	inch millimeter	See Note 1			



				One of the most popular gage sizes.			
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH	J2A-XX-S033P-350 J2A-XX-S182K-10C N2K-XX-S081P-20C/DP TK-XX-S081P-20C/DP J5K-XX-S100P-350/DP	350 ± 0.3% 1000 ± 0.3% 2000 ± 0.3% 2000 ± 0.3% 350 ± 0.3%	P K P P P	E2 E2
MATRIX SIZE	0.28 L x 0.16 W	7.1 L x 4.1 W					



				Tabs at both ends of grid for simplified wiring on some transducer designs.			
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH	N2A-XX-S044Q-350	350 ± 0.15%	Q	E2
0.125	0.255	0.125	0.125				
3.18	6.48	3.18	3.18				
MATRIX SIZE	0.32 L x 0.19 W	8.1 L x 4.7 W					




				Narrow, encapsulated version of S044.			
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH	J2A-XX-S113M-350	350 ± 0.3%	M	
0.110	0.285	0.080	0.080				
2.82	7.31	2.03	2.03				
MATRIX SIZE	0.34 L x 0.14 W	8.7 L x 3.6 W					

Note 1: Products shown in bold are not RoHS compliant.

Transducer-Class® Strain Gages

GAGE PATTERN	Actual size shown. Enlarged when necessary for definition		GAGE DESIGNATION See Note 1	RES. IN OHMS	STANDARD CREEP CODE	ENCAPSULATION OPTION AVAILABLE
	DIMENSIONS	inch millimeter				



Narrow-grid version of T004/T005.


GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH			
0.125	0.20	0.060	0.070			
3.18	5.1	1.52	1.78			
MATRIX SIZE	0.27 L x 0.12 W		6.9 L x 3.0 W			

N2A-XX-T019M-350
 J2A-XX-S038M-350
 N2K-XX-T020T-350/DP
 TK-XX-T020T-350/DP

350 \pm 0.15%
 350 \pm 0.3%
 350 \pm 0.15%
 350 \pm 0.15%

M
 M
 T
 T

E2
 E2



Longer grid for strain averaging or where higher power dissipation is required.


GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH			
0.250	0.37	0.125	0.125			
6.35	9.4	3.18	3.18			
MATRIX SIZE	0.44 L x 0.19 W		11.2 L x 4.8 W			

N2A-XX-T007R-350
 J2A-XX-S109M-350
 N2K-XX-T008R-350/DP
 TK-XX-T008R-350/DP

350 \pm 0.15%
 350 \pm 0.3%
 350 \pm 0.15%
 350 \pm 0.15%

R
 M
 R
 R

E2
 E2



Large grid and high resistance permit higher-than-normal excitation voltage.

GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH			
0.250	0.36	0.175	0.175			
6.35	9.1	4.45	4.45			
MATRIX SIZE	0.42 L x 0.24 W		10.7 L x 6.1 W			

N2A-XX-S051R-10C

1000 \pm 0.15%

R

E2

Note 1: Products shown in bold are not RoHS compliant.